

TRANSLATORS

Translatori

EKTI 1
EKTI 2
EKTI 3
EKTI 4



Railway Infrastructure

Type / Tip	Cat. No. / Kat. br.	Whitpaper No. / Kat. List br.	Impedance ratio / Omjer impedancija
EKT11	5E 01460	E06050	600 Ohma : 600 Ohma
EKT12	5E 01459	E06064	600 Ohma : 1200 Ohma
EKT13	5E 01485	E06065	600 Ohma : 1500 Ohma
EKT14	5E 01486	E06066	2000 Ohma : 5000 Ohma

Transformation ratio tolerance / Tolerancija prijenosnog omjera	1 %
Rated frequency response / Nazivno frekvencijsko područje	100 Hz – 4 kHz
Rated frequency range damping factor / Gušenje u nazivnom frekventnom području	< 0,44 dB
Impedance at 25 Hz dialing frequency / Impedancija kod pozivne frekvencije 25 Hz	> 20 k
Symetrical damping factor at 3.4 kHz / Simetrijsko prigušenje kod 3,4 kHz	> 78 dB
Overhearing between translators damping factor / Prigušenje preslušavanja između dva translatora	> 90 dB
The efficiency / Postotak korisnog djelovanja	> 80 %
Test voltage / Ispitni napon	4 kV, 50 Hz
Insulation resistance to casing / Izolacioni otpor prema kućištu	> 10000 M
Operating ambient temperature / Radna temperatura okoline	-25 °C to + 70 °C / -25 °C do + 70 °C
Width / Širina	72 mm
Height / Visina	98 mm
Length / Dubina	52 mm
Weight / Masa	990 g

CONTROL AND
SIGNALLING
TECHNOLOGY

ELEKTROKEM



industrijska elektronika

A. Šenoa 69, Vugrovec, 10360 Sesvete, Hrvatska
tel. +385 1 2051 400, fax. +385 1 2051 406
elektrokem@elektrokem.hinet.hr
http://www.elektrokem.hr

Kataloški list br. E06067